


Fire resistance classes for use as wall elements															
 Product	Fire resistance class		max. span [m]						Type	Element thickness (D) [mm]	required cover shell thickness ¹⁾ (t _{nom}) [mm]		Test report		
			Option 1 (in accordance with EN 14 509 and EN 1364-1)			Option 2 (in accordance with EN 15 254-5 *)									
					orientation: v = vertical h = horizontal						orientation: v = vertical h = horizontal				
			partition	external wall	v	h	v	h			outside	inside			
Hoesch isorock vario FIREtec®	EN 13501-2	EI 120	EI 120 (o ↔ i)	≤ 4,00	X					S2-01	≥ 150	0,55 to 0,95	0,55 to 0,95	FIRES-CR-149-18-AURE and FIRES-CR-150-18-AURE	
		EW 120	EW 120 (o ↔ i)		X										
		EI 90	EI 90 (o ↔ i)	≤ 4,00	X	X	≤ 7,50		X		S2-01	≥ 120	0,55 to 0,95	0,55 to 0,95	FIRES-CR-149-18-AURE, FIRES-CR-150-18-AURE, FIRES-CR-151-18-AURE, FIRES-CR-152-18-AURE
		EW 90	EW 90 (o ↔ i)		X	X			X						
		EI 90	EI 90 (o ↔ i)	≤ 4,00		X					S2-01	≥ 120	0,55 to 0,95	0,55 to 0,95	FIRES-CR-151-18-AURE and FIRES-CR-152-18-AURE
		EW 90	EW 90 (o ↔ i)			X									
		EI 60	EI 60 (o ↔ i)	≤ 4,00	X	X	≤ 7,50		X	X	S2-01	≥ 120	0,55 to 0,95	0,55 to 0,95	FIRES-CR-153-18-AURE, FIRES-CR-156-18-AURE, FIRES-CR-151-18-AURE, FIRES-CR-152-18-AURE
		EW 60	EW 60 (o ↔ i)		X	X			X	X					
		EI 30	EI 30 (o ↔ i)	≤ 4,00	X	X	≤ 7,50		X	X	S2-01	≥ 120	0,55 to 0,95	0,55 to 0,95	FIRES-CR-151-18-AURE, FIRES-CR-155-18-AURE, FIRES-CR-156-18-AURE, FIRES-CR-157-18-AURE
		EW 30	EW 30 (o ↔ i)		X	X			X	X					
		E 90 (o ← i)	EI 90-ef (o → i)	≤ 4,00	X	X	≤ 6,00			X	S2-01	≥ 120	0,60	0,60	FIRES-CR-151-18-AURE, FIRES-CR-155-18-AURE, FIRES-CR-156-18-AURE, FIRES-CR-157-18-AURE
		EW 90 (o ← i)	EW 90-ef (o → i)		X	X				X					
			EI 240-ef (o → i)	≤ 4,00	X	X	≤ 6,00		X	X	S2-01	≥ 120	0,60	0,60	FIRES-CR-155-18-AURE and FIRES-CR-157-18-AURE
			EW 240-ef (o → i)		X	X			X	X					
			EI 60 (o ← i)	≤ 4,00	X		≤ 6,00		X		S2-01	≥ 100	0,55 to 0,95	0,55 to 0,95	FIRES-CR-158-18-AURE
			EW 60 (o ← i)		X				X						
			EI 30	EI 30 (o ↔ i)	≤ 4,00	X		≤ 7,50		X	S2-01	≥ 100	0,55 to 0,95	0,55 to 0,95	FIRES-CR-158-18-AURE and FIRES-CR-159-18-AURE
			EW 30	EW 30 (o ↔ i)		X				X					
				EI 240-ef (o → i)	≤ 4,00		X	≤ 6,00			S2-01	≥ 80	0,55 to 0,95	0,55 to 0,95	FIRES-CR-160-18-AURE
				EW 240-ef (o → i)			X								
				EI 180-ef (o → i)	≤ 4,00		X				S1-01	≥ 120	0,55 to 0,95	0,55 to 0,95	FIRES-CR-161-18-AURE
				EW 180-ef (o → i)			X								
				E 120 (o ← i)	≤ 4,00		X	≤ 7,50		X	S1-01	≥ 120	0,55 to 0,95	0,55 to 0,95	FIRES-CR-161-18-AURE and FIRES-CR-162-18-AURE
				EW 120 (o ← i)			X			X					
				E 90 (o ← i)	≤ 4,00		X	≤ 7,50		X	S1-01	≥ 120	0,55 to 0,95	0,55 to 0,95	FIRES-CR-161-18-AURE and FIRES-CR-162-18-AURE
				EW 90 (o ← i)			X			X					
				EI 60 (o ← i)	≤ 4,00		X	≤ 7,50		X	S1-01	≥ 120	0,55 to 0,95	0,55 to 0,95	FIRES-CR-161-18-AURE and FIRES-CR-162-18-AURE
				EW 60 (o ← i)			X			X					

¹⁾ min. and max. cover sheet thickness. Outside the tolerance range no fire resistance class of the elements.

* EN 15254-5, Extended application of results from fire resistance tests